

ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829



# Safety Data Sheet dated 1/2/2013, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1. Product identifier	
Mixture identification:	
Trade name: SCIOGLI SILICONE	
Trade code: 80.0015	
1.2. Relevant identified uses of the substance or mixture and uses advised against	
Recommended use:	
Spray painting decorative household, industrial and professional	
1.3. Details of the supplier of the safety data sheet	
Company:	
ARECO ITALIA SPA Via Dell'Industria 72/74 20083 Vigano di Gaggiano (MI) ARECO ITALIA SPA TEL. +39 029085372 - +39 029086270	
Competent person responsible for the safety data sheet:	
info@arecoitalia.it	
1.4. Emergency telephone number	
ARECO ITALIA SPA TEL. +39 029085372 - +39 029086270	
SECTION 2: Hazards identification	
2.1. Classification of the substance or mixture	
Directive criteria, 67/548/CE, 99/45/EC and following amendments thereof:	
Properties / Symbols:	
F+ Extremely flammable	
Xi Irritant	
N Dangerous for the environment R Phrases:	
R12 Extremely flammable.	
R38 Irritating to skin.	
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquati	с
environment.	0
R67 Vapours may cause drowsiness and dizziness.	
Adverse physicochemical, human health and environmental effects: No other hazards	
2.2. Label elements	
Xi F+ N	
Symbols:	
Xi Irritant	
F+ Extremely flammable	
N Dangerous for the environment	
R Phrases:	
R12 Extremely flammable.	
R38 Irritating to skin.	

80.0015/1 Page n. 1 of 9



ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67 Vapours may cause drowsiness and dizziness.

S Phrases:

S2 Keep out of reach of children.

S23 Do not breathe spray.

S29/56 Do not empty into drains, dispose of this material and its container to hazardous or special waste collection point.

S43 In case of fire, use vaporized water or foam.

S46 If swallowed, seek medical advice immediately and show this container or label.

S9 Keep container in a well-ventilated place.

### **Special Provisions:**

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of reach of children.

### 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

### Other Hazards:


No other hazards

### **SECTION 3: Composition/information on ingredients**

- 3.1. Substances N.A.
- 3.2. Mixtures

Hazardous components within the meaning of EEC directive 67/548 and CLP regulation and related classification:

- 30% 40% hexane, reaction mass of isomers (containing < 5 % n-hexane (203-777-6)) Index number: 601-007-00-7, CAS: 107-83-5, EC: 203-523-4
  - F,Xn,Xi,N; R11-38-51/53-65-67
    - 2.6/2 Flam. Liq. 2 H225
    - 3.10/1 Asp. Tox. 1 H304
    - (1) 3.2/2 Skin Irrit. 2 H315



- 3.8/3 STOT SE 3 H336
- 25% 30% heptane; n-heptane;



- 3.2/2 Skin Irrit. 2 H315
- (1) 3.8/3 STOT SE 3 H336

80.0015/1 Page n. 2 of 9




ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

4.1/A1 Aquatic Acute 1 H400

- 4.1/C1 Aquatic Chronic 1 H410
- 20% 25% propane

Index number: 601-003-00-5, CAS: 74-98-6, EC: 200-827-9 F+; R12; substance with a Community workplace exposure limit 2.2/1 Flam. Gas 1 H220



10% - 12.5% butane

Index number: 601-004-00-0, CAS: 106-97-8, EC: 203-448-7 F+; R12; substance with a Community workplace exposure limit 2.2/1 Flam. Gas 1 H220



2.5 Press. Gas H280

3% - 5% butane

Index number: 601-004-00-0, CAS: 75-28-5, EC: 200-857-2 F+; R12; substance with a Community workplace exposure limit 2.2/1 Flam. Gas 1 H220

2.5 Press. Gas H280

### **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Areas of the body that have - or are only even suspected of having - come into contact with the product must be rinsed immediately with plenty of running water and possibly with soap. Wash thoroughly the body (shower or bath).

Remove contaminated clothing immediatley and dispose off safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed None
- 4.3. Indication of any immediate medical attention and special treatment needed

80.0015/1 Page n. 3 of 9



ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Treatment: None

## **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

- Suitable extinguishing media:
  - In case of fire, use vaporized water or foam.
  - Extinguishing media which must not be used for safety reasons:
  - None in particular.
- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

### **SECTION 6: Accidental release measures**

- 6.1. Personal precautions, protective equipment and emergency procedures Wear personal protection equipment.
  - Remove all sources of ignition.
  - Remove persons to safety.
  - See protective measures under point 7 and 8.
- 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recomened protective equipment.

- 7.2. Conditions for safe storage, including any incompatibilities
  - Always keep in a well ventilated place.

Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.

Keep away from food, drink and feed.

80.0015/1 Page n. 4 of 9



#### ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

# Safety Data Sheet SCIOGLI SILICONE

Incompatible materials: None in particular. Instructions as regards storage premises: Cool and adequately ventilated. 7.3. Specific end use(s) None in particular

**SECTION 8: Exposure controls/personal protection** 8.1. Control parameters heptane; n-heptane; - CAS: 142-82-5 TLV TWA - ppm 400 TLV STEL - ppm 500 VLE 8h - ppm 500 mg/m3 2085 propane - CAS: 74-98-6 TLV TWA - 1000 ppm - 0 mg/m3 VLE short - 1000 ppm butane - CAS: 106-97-8 TLV TWA - 1000 ppm butane - CAS: 75-28-5 TLV TWA - 1000 ppm - 0 mg/m3 VLE short - 1000 ppm **DNEL Exposure Limit Values** N.A. **PNEC Exposure Limit Values** N.A. 8.2. Exposure controls Eye protection: Not needed for normal use. Anyway, operate according good working practices. Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber. Respiratory protection: Use adequate protective respiratory equipment. Thermal Hazards: None Environmental exposure controls: None

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties Appearance and colour: Liquid aspect (under pressure), various colours.

Odour:Caracteristic of solventOdour threshold:N.A.pH:N.A.Melting point / freezing point:N.A.Initial boiling point and boiling range:N.A.Solid/gas flammability:Extremely flammableUpper/lower flammability or explosive limits:N.A.



Vanaur danaitur

ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

N I A

Vapour density:	N.A.
Flash point:	Inf. 0 ° C
Evaporation rate:	N.A.
Vapour pressure:	a 20°C - 3,5 bar
Relative density:	0,75 - 0,80 g/ml
Solubility in water:	N0
Solubility in oil:	SI
Partition coefficient (n-octanol	/water): N.A.
Auto-ignition temperature:	N.A.
Decomposition temperature:	N.A.
Viscosity:	N.A.
Explosive properties:	N.A.
Oxidizing properties:	N.A.
.2. Other information	
Miscibility:	N.A.
Fat Solubility:	N.A.
Conductivity:	N.A.
Substance Groups relevant pr	operties N.A.

## **SECTION 10: Stability and reactivity**

10.1. Reactivity

9.

- Stable under normal conditions
- 10.2. Chemical stabilityStable under normal conditions10.3. Possibility of hazardous reactions
- 10.3. Possibility of hazardous reactions None
- 10.4. Conditions to avoid Stable under normal conditions.10.5. Incompatible materials
  - Avoid contact with combustible materials. The product could catch fire.
- 10.6. Hazardous decomposition products None.

#### **SECTION 11: Toxicological information**

11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

N.A.

If not differently specified, the information required in Regulation 453/2010/EC listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

d) respiratory or skin sensitisation;

e) germ cell mutagenicity;

f) carcinogenicity;

g) reproductive toxicity;

h) STOT-single exposure;

i) STOT-repeated exposure;

j) aspiration hazard.

80.0015/1 Page n. 6 of 9



ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

# **SECTION 12: Ecological information**

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- N.A.
- 12.2. Persistence and degradability
  - None
  - N.A.
- 12.3. Bioaccumulative potential
- N.A. 12.4. Mobility in soil
  - N.A.
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
  12.6. Other adverse effects
  - None

## **SECTION 13: Disposal considerations**

13.1. Waste treatment methods Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## **SECTION 14: Transport information**



- 14.1. UN number
- 14.2. UN proper shipping name ADR-Shipping Name: IATA-Shipping Name: IMDG-Shipping Name:
- 14.3. Transport hazard class(es)
- 14.4. Packing group
- 14.5. Environmental hazards
- 14.6. Special precautions for user
- 14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code N.A.

## **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances)

\*ENTER PROPER SHIPPING NAME\*

\*ENTER PROPER SHIPPING NAME\*

\*ENTER PROPER SHIPPING NAME\*

- Dir. 99/45/EC (Classification, packaging and labelling of dangerous preparations)
- Dir. 98/24/EC (Risks related to chemical agents at work)
- Dir. 2000/39/EC (Occupational exposure limit values)
- Dir. 2006/8/EC

80.0015/1 Page n. 7 of 9



ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

# Safety Data Sheet SCIOGLI SILICONE

Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) Regulation (EU) n. 453/2010 (Annex I) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: None Volatile CMR substances = 0.00 % Halogenated VOCs which are assigned the risk phrase R40 = 0.00 % Organic Carbon - C = 0.00 Where applicable, refer to the following regulatory provisions : Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments. Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical safety assessment No

### **SECTION 16: Other information**

Text of phrases referred to under heading 3:

R11 Highly flammable.

R12 Extremely flammable.

R38 Irritating to skin.

R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R65 Harmful: may cause lung damage if swallowed.

R67 Vapours may cause drowsiness and dizziness.

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H411 Toxic to aquatic life with long lasting effects.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU. This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.



ARECO ITALIA S.p.A. Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Áviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization"
	(ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day.
	(ACGIH Standard).
WGK:	German Water Hazard Class.
N.A.:	N.A.
N.D.:	