

**DATE: DECEMBER 2008****TECHNICAL DATASHEET****PRODUCT: OIL ANTIRUST LUBRICANT FOR ALL USES GPL****CODE: 50.0008**

**PROPERTIES AND AREAS OF USE:** Unlocking and rust-preventing oil useful for fire arms, cars, drilling – lapping – and sewing machines, fishing reels, rolling shutters (for windows), doors and door-locks and for all rusted parts of any kind of object – tool and mechanism.

**It contains no chlorinated solvents.**

**SUPPLY SPECIFICATIONS:**

**15 bar foil-coated can  
Net content**

**400 ml**

**Appearance**

**Liquid appearance**

**Colour**

**Colourless**

**Scent**

**Typical solvent**

**Density at 20°C**

**0.75 - 0.80 g/ml**

**Flammability point**

**less than 0° C**

**Pressure at 20°C**

**4,0 ± 0,5 bar**

**Pressure at 50°C**

**8,0 ± 0,5 bar**

**LABELLING:**

**IRRITANT**



**HIGHLY  
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.