

DATE: January 2010

TECHNICAL DATASHEET

PRODUCT: ZINC SPRAY PAINT**CODE:** 70.0060/EcoDie

PROPERTIES AND AREAS OF USE: The content of zinc metal coating forms a highly corrosion resistant weathering. Protects tanks, pylons, joints welded bars, works of carpentry. Indicated after operations threading, cutting or welding to restore the corrosion resistance.

The 400 ml bottle covers an area of 1.5 - 2 meters, depending on the nature of support.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can**Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****13"****From 20%****From 6 to 7 Micron****12 Gloss****7 Micron****36 Micron****120°C****10 minutes****20 minutes****24 hours**

LABELLING:

**HIGHLY
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.