

**DATE: MAY 2007**

## **TECHNICAL DATASHEET**

**PRODUCT: SPRAY PRIMER-FILLER****CODE: 35.023**

**PROPERTIES AND AREAS OF USE:** For filling small scratches and imperfections. Suitable for bodywork or metal surfaces. Rub over with very fine sandpaper before repainting, if necessary.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the colour of the paint.

### **SUPPLY SPECIFICATIONS:**

**15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0° C****10 minutes****20 minutes****24 hours****Directive 2004/42/CE: C.O.V.**

Subcategory: Special finishes

COV value limit: 840 g/Litre

Max. actual contents: 640 g/Litre

### **LABELLING:**

**IRRITANT****HIGHLY  
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.