

TECHNICAL DATASHEET**PRODUCT: STEEL SPRAY PAINT****CODE: 70.0050**

PROPERTIES AND AREAS OF USE: Stainless steel is one of the materials which is most resistant to atmospheric agents, saline corrosion and acid rain. This makes it perfect for protecting items which are subject to attack by these elements. Protective roofing elements, rainwater pipes, gates and wrought iron are preserved by the combination of metallic pigment with acrylic resins, both of which offer perfect resistance to the most severe conditions.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can	400 ml
Net content	Can containing pressurised liquid
Appearance	Typical
Colour	Typical solvent
Scent	0.75 - 0.80 g/ml
Density at 20°C	4.0 ± 0.5 bar
Pressure at 20°C	8.0 ± 0.5 bar
Pressure at 50°C	less than 0°C
Flammability point	From 12" to 14"
Viscosity Ford Cup 4	15%
Remaining dry cylinder	From 6 to 7 Micron
Grit to grindometro	5 Gloss
Gloss	12 Micron
Thickness 1 hand	30 Micron
Thickness 3 hands	100 – 130°C
Temperature resistance	
Drying time:	
Dust resistant	10 minutes
Dry to touch	20 minutes
Fully dry	24 hours
May be painted over at any time	
Childproof patented safety cap	
Colour reference patch	

LABELLING:**IRRITANT****HIGHLY
INFLAMMABLE**