

**TECHNICAL DATASHEET****PRODUCT: FAST-DRYING ACRYLIC SPRAY PAINT****CODE: 35.000**

**PROPERTIES AND AREAS OF USE:** Acrylic paint designed especially to satisfy the needs of professional users. It possesses excellent adhesion characteristics and is suitable for painting metallic materials (iron, brass, aluminium), plastic material, machine tools, doors, windows and shutters. Fast drying and the fact that it can be painted over make it the ideal tool for hobbies and crafts as well as industry.

Features: excellent coverage, non-yellowing, durable, colourfast and lead-free pigments, fast drying, CFC-free.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the colour of the paint.

**SUPPLY SPECIFICATIONS:****15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****From 11" to 12,5"****From 12% to 23,8%****From 0 to 2 Micron****From 7 to 92 Gloss****11 Micron****32 Micron****100 – 120°C****10 minutes****20 minutes****24 hours****LABELLING:****Directive 2004/42/CE: C.O.V.**

Subcategory: Special finishes

COV value limit: 840 g/Litre

Max. actual contents: 640 g/Litre

**IRRITANT****HIGHLY  
INFLAMMABLE**