

ARECO ITALIA S.p.A.

Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

DATE: January 2010

TECHNICAL DATASHEET

PRODUCT: ACRYLIC FIXATIVE SPRAY VARNISH

CODE: 80.024

PROPERTIES AND AREAS OF USE: Transparent acrylic varnish designed to provide a protective finish for watercolours, poster paints, charcoals and pastels. It does not alter drawings and protects them against dust, damp and accidental rubbing. It can also be used to protect frames and other wooden items.

The 400 ml can covers an area of 1.5 - 2 m², depending on the colour of the paint.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can Net content Appearance Colour Scent Density at 20℃ Pressure at 20℃ Pressure at 50℃ Flammability point **Viscosity Ford Cup 4** Remaining dry cylinder Grit to grindometro Gloss Thickness 1 hand **Thickness 3 hands Temperature resistance** Drying time: **Dust resistant** Dry to touch Fully dry May be painted over at any time Childproof patented safety cap **Colour reference patch**

400 ml Can containing pressurised liquid Miscellaneous **Typical solvent** 0.75 - 0.80 g/ml 4.0 ± 0.5 bar 8.0 ± 0.5 bar less than 0°C 11'.2' 17,50% Ω 90 Gloss 7 Micron 23 Micron 90 – 100℃ 10 minutes 20 minutes 24 hours

LABELLING:



IRRITANT



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breech of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.