

**DATE: January 2010**

## **TECHNICAL DATASHEET**

**PRODUCT: RUST PROOFING SPRAY PAINT****CODE: 35.022**

**PROPERTIES AND AREAS OF USE:** Offers metal surfaces lasting protection against rust. It can be painted over with the original paint, but only after the first coat has dried. The acrylic resins contained make it suitable for indoor and outdoor use, guaranteeing resistance against atmospheric agents.

### **SUPPLY SPECIFICATIONS:**

**15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****11,4"****21,50%****From 0 to 2 Micron****From 25 to 30 Gloss****13 Micron****35 Micron****100 – 120°C****10 minutes****20 minutes****24 hours**

### **LABELLING:**

**IRRITANT****HIGHLY  
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.