

ARECO ITALIA S.p.A.

Via Dell'Industria, 72/74 20083 VIGANO DI GAGGIANO (MI) Tel. (02) 90.85.372 - 90.86.270 Fax (02) 90.81.829

DATE: January 2010

## **TECHNICAL DATASHEET**

## **PRODUCT: STAIN SPRAY**

CODE: 35.021

**PROPERTIES AND AREAS OF USE:** Matt white acrylic paint to cover and eliminate stains on walls in preparation for painting. Smoke, soot, dirt, grease, pencil or felt tip pen are all easily hidden and the surface is ready for painting after a minimum of half an hour.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the type of element to be painted.

## **SUPPLY SPECIFICATIONS:**

15 bar foil-coated can Net content Appearance Colour Scent Density at 20℃ Pressure at 20°C Pressure at 50℃ Flammability point **Viscosity Ford Cup 4** Remaining dry cylinder Grit to grindometro Gloss **Thickness 1 hand** Thickness 3 hands **Temperature resistance** Drying time: **Dust resistant** Dry to touch Fully dry May be painted over at any time Childproof patented safety cap **Colour reference patch** 

400 ml Can containing pressurised liquid Miscellaneous **Typical solvent** 0.75 - 0.80 g/ml 4.0 ± 0.5 bar 8.0 ± 0.5 bar less than 0°C 12" 23.80% From 0 to 2 Micron From 6 to 7 Gloss 15 Micron 35 Micron 100 – 120℃ 10 minutes

20 minutes 24 hours

LABELLING:



IRRITANT



Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breech of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.