

**TECHNICAL DATASHEET****PRODUCT: FERRO-MICACEOUS SPRAY PAINT****CODE: 40.000**

**PROPERTIES AND AREAS OF USE:** Extra-thick acrylic paint, ideal for treating ferrous surfaces, both new and already partially attacked by atmospheric agents.

The special corrosion block contained offers excellent long-term protection and the matt appearance is typical of old iron.

This makes it ideal for gates, protective roofing elements, ferrous pipes, scaffolding, rainwater pipes and doors.

In industrial maintenance too, it is recommended for its practicality and particular resistance to corrosion.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the colour of the paint.

**SUPPLY SPECIFICATIONS:****15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****12"****From 19% to 22,2%****From 8 to 23 Micron****From 7 to 45 Gloss****25 Micron****50 – 60 Micron****100 – 130°C****10 minutes****20 minutes****24 hours****LABELLING:****IRRITANT****HIGHLY  
INFLAMMABLE**