

DATE: January 2010

TECHNICAL DATASHEET

PRODUCT: OIL PAINTING TOPCOAT SPRAY VARNISH**CODE: 80.023**

PROPERTIES AND AREAS OF USE: Clear ketonic varnish made specifically to protect oil paintings from the action of external agents, such as dust, light, humidity or manipulation which would damage the painting.

It can also be used to enhance frames or other wooden objects.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can**Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****11"****17,50%****0****90 Gloss****6 Micron****22 Micron****90 – 100°C****10 minutes****20 minutes****24 hours**

LABELLING:

**IRRITANT****HIGHLY
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.