

DATE: January 2010**TECHNICAL DATASHEET****PRODUCT: SPRAY VARNISH FOR WOOD****CODE: 35.001/1**

PROPERTIES AND AREAS OF USE: Protective clear varnish for application to stripped, dry wood. Protects against dust and atmospheric agents, preserving the natural appearance of the sprayed object. Also suitable for imitation or dried flowers, fabrics, ornaments and ceramics.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:**15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****11''****From 12% to 13%****From 0 to 2 Micron****From 18 to 85 – 90 Gloss****8 Micron****28 Micron****100°C****10 minutes****20 minutes****24 hours****LABELLING:****IRRITANT****HIGHLY
INFLAMMABLE**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.