

DATE: January 2010

TECHNICAL DATASHEET

PRODUCT: SPRAY PAINT FOR MARKING**CODE: 20.000**

PROPERTIES AND AREAS OF USE - Acrylic-based paint: its' fast drying, firm adhesion to surfaces and resistance to rubbing and friction make it ideal for tracing, marking or outlining spaces, areas, corridors in worksites, workshops, roads, car parks, sports facilities, wood or pallets.

The 400 ml can covers an area of 1.5 - 2 m², depending on the colour of the paint and the type of element to be painted.

SUPPLY SPECIFICATIONS:

15 bar foil-coated can**Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Miscellaneous****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****From 11,3" to 11,8"****From 18% to 23,8%****From 0 to 2 Micron****From 8 to 15 Gloss****15 Micron****35 Micron****100 – 120°C****10 minutes****20 minutes****24 hours**

LABELLING:

**IRRITANT****HIGHLY
INFLAMMABLE**