

**DATE: MAY 2007**

## **TECHNICAL DATASHEET**

**PRODUCT: EXTRA-THICK GALVANISING SPRAY PAINT      CODE: 70.0082**

**PROPERTIES AND AREAS OF USE:** Extra-thick acrylic paint, containing pure zinc, when high-level protection is required.

The layer of paint applied offers excellent resistance to the most severe stress, including atmospheric stress, and is therefore recommended for the protection of ferrous items located outdoors.

The result is 30% thicker than that usually supplied by similar paints available on the market.

The 400 ml can covers an area of 1.5 - 2 m<sup>2</sup>, depending on the type of element to be painted.

### **SUPPLY SPECIFICATIONS:**

**15 bar foil-coated can**

**Net content**

**Appearance**

**Colour**

**Scent**

**Density at 20°C**

**Pressure at 20°C**

**Pressure at 50°C**

**Flammability point**

**Coverage:**

**Drying time:**

**Dust resistant**

**Dry to touch**

**Fully dry**

**May be painted over at any time**

**Childproof patented safety cap**

**Colour reference patch**

**400 ml**

**Can containing pressurised liquid**

**Miscellaneous**

**Typical solvent**

**0.75 - 0.80 g/ml**

**4.0 ± 0.5 bar**

**8.0 ± 0.5 bar**

**less than 0° C**

**about 1.5 – 2 m<sup>2</sup> per can**

**10 minutes**

**20 minutes**

**24 hours**

### **LABELLING:**



**NOXIOUS**



**HIGHLY  
INFLAMMABLE**



**HARMFUL TO  
THE ENVIRONMENT**

Despite being considered reliable, this information is merely issued as a guideline. Its use implicates no liability by our company, including the breach of any patents or licenses. The user is responsible for checking that the product is suitable for the specific use.