

TECHNICAL DATASHEET**PRODUCT: DARK GALVANISING SPRAY PAINT****CODE: 70.0070**

PROPERTIES AND AREAS OF USE: The high zinc content and special acrylic resins used lend the protective layer an effective barrier against atmospheric agents and salt. It can be used on pylons, pipes, tanks, metallic elements or welding joints to provide resistance to corrosion.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:**15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Percentage of zinc on the dry weight****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Typical****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****13"****20,65%****20,1 %****From 6 to 7 Micron****9 Gloss****12 Micron****30 Micron****120°C****10 minutes****20 minutes****24 hours****LABELLING:****HIGHLY
INFLAMMABLE****HARMFUL TO
THE ENVIRONMENT**