


DATE: January 2010**TECHNICAL DATASHEET****PRODUCT: GALVANISING SPRAY PAINT****CODE: 70.0039**

PROPERTIES AND AREAS OF USE: The zinc contained forms a high-resistance metallic coating resistant to corrosion by atmospheric agents. It effectively protects tanks, pylons, welded joints, window bars and other metal elements. Also suitable after threading, cutting or welding operations to restore resistance to corrosion.

The 400 ml can covers an area of 1.5 - 2 m², depending on the type of element to be painted.

SUPPLY SPECIFICATIONS:**15 bar foil-coated can****Net content****Appearance****Colour****Scent****Density at 20°C****Pressure at 20°C****Pressure at 50°C****Flammability point****Viscosity Ford Cup 4****Remaining dry cylinder****Percentage of zinc on the dry weight****Grit to grindometro****Gloss****Thickness 1 hand****Thickness 3 hands****Temperature resistance****Drying time:****Dust resistant****Dry to touch****Fully dry****May be painted over at any time****Childproof patented safety cap****Colour reference patch****400 ml****Can containing pressurised liquid****Typical****Typical solvent****0.75 - 0.80 g/ml****4.0 ± 0.5 bar****8.0 ± 0.5 bar****less than 0°C****From 14" to 18"****25,40%****7,5 %****From 6 to 7 Micron****12 Gloss****7 Micron****36 Micron****120°C****10 minutes****20 minutes****24 hours****LABELLING:****HIGHLY
INFLAMMABLE****HARMFUL TO
THE ENVIRONMENT**